



Express Mail No. EV 130050048 US  
GECAN-3214  
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Ong et. al. :  
Serial No.: 09/681,253 : Art Unit: 2834  
Filed: March 8, 2001 : Examiner: Waks, J.  
For: STATOR, DYNAMOELECTRIC :  
MACHINE, AND METHODS :  
FOR FABRICATING SAME :

SUBMISSION OF MARKED UP CLAIMS

Hon. Commissioner for Patents  
Washington, D.C. 20231

Submitted herewith are marked up claims in accordance with 37 C.F.R. 1.121(c)(1)(ii).

IN THE CLAIMS

5. (once amended) A method [according to Claim 1 wherein said step of] for facilitating a fabrication of a high temperature superconducting electrical machine, said method comprising the steps of:

fabricating a back iron;

attaching a plurality of non-magnetic teeth to the back iron with at least one key, said plurality of non-magnetic teeth [further comprises the step of attaching a plurality of non-magnetic teeth] comprising at least one of [a glass laminate,] a carbon fiber[,] and a fiber polymer;

and installing the back iron in the machine [to the back iron with at least one key].

RECEIVED  
AUG 12 2002  
TECHNOLOGY CENTER 2800

6. (once amended) [A method according to Claim 1 wherein] A method for facilitating a fabrication of a high temperature superconducting electrical machine, said method comprising the steps of:

fabricating a back iron;

attaching a plurality of non-magnetic teeth to the back iron wherein [said step of attaching a plurality of non-magnetic teeth further comprises the step of attaching] at least one non-magnetic tooth [including] includes at least one embedded conductor; and

installing the back iron in the machine.


7. (once amended) A method for fabricating a stator with non-magnetic teeth, said method comprises the steps of:

fabricating a back iron; and

attaching a non-magnetic tooth back portion comprising a plurality of non-magnetic teeth to the back iron.

10. (once amended) A method according to Claim 7 wherein said step of attaching a plurality of non-magnetic teeth further comprises the step of attaching a plurality of non-magnetic teeth comprising at least one of [a glass laminate,] a carbon fiber[,], and a fiber polymer to the back iron.

Respectfully Submitted,



Thomas M. Fisher  
Registration No. 47,564  
ARMSTRONG TEASDALE LLP  
One Metropolitan Square, Suite 2600  
St. Louis, Missouri 63102-2740  
(314) 621-5070